

ventus

Lightweight Fiberglass Tender



8VL

	Overal Length	:	8´6"/ 2.60m	Number of Chambers	:	3 + 1	Shaft Length	:15"/38.1cm
SPECS	Overal Beam	:	5´6"/ 1.68m	Person Capacity	:	4	RDC Design Category	: C
	Inside Length	:	5´10"/ 1.79m	Weight	:	95lb / 43kg		
	Inside Beam	:	2′4″/ 0.72m	Recommended HP	:	8hp / 6kw		
	Tube Diameter	:	16"/ 0.40m	Maximum HP	:	10hp / 7.5kw		

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Non Skid Rubber Floor Pannels

- Plastic External Transom Plate
- Plastic External Plate
 Aluminum Internal Transom Plate with Security Lip
 Stainless Steel Bow Eye
 Stainless Steel 3 Davit Lifting Points
 Inner Hull Drain with Plug

- Deck Condensation PlugOrca(CSM) Five Layer Coated Fabric

Removable Rowing Seat

- Raised Single Rub Rail

- 3 Layer Reinforced Seams

л N ∢ш Zĸ 0⊃ \vdash

- ∢ പപ Оц

ΔS പ ന

ЧЧ

 $\Box \supset$

zμ < < ⊢ш

мщ

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat



- Lateral Fold Down Stainless Steel Cleat
- Oarlock Bases
 Telescopic Oars with Aluminum Shaft
 Paddle Holders Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Hand Pump
 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
 Owner's Manual
 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor