

## ventus

## Lightweight Fiberglass Tender



9VL

	Overal Length	:	9´6″/ 2.90m	Number of Chambers	: 3+1	Shaft Length	:15″/38.1cm
SPECS	Overal Beam	:	5′7″/ 1.72m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	:	6´9″/ 2.06m	Weight	: 106lb / 48kg		
	Inside Beam	:	2´8″/ 0.81m	Recommended HP	: 9.9hp / 7.4kw		
	Tube Diameter	:	17″/ 0.43m	Maximum HP	:15hp / 11.2kw		

- Hand Laid Fiberglass Deep "V" Hull
  Stringer System Laminated into Hull
  Non Skid Rubber Floor Pannels

- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip Stainless Steel Bow Eye Stainless Steel 3 Davit Lifting Points
- - Inner Hull Drain with Plug

- Deck Condensation Plug
- Orca(CSM) Five Layer Coated Fabric Raised Single Rub Rail

- Oarlock Bases Telescopic Oars with Aluminum Shaft Paddle Holders
- Padde Holders
  Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
  Hand Pump
  1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
  2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
  2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
  Removable Rowing Seat
  Additional Air Retaining Chamber Under the Floor
  3 Layer Reinforced Seams

## പഗ ⊲ ш Zĸ 0⊃

 $\vdash$ - ∢

പപ Оц

ΔS പ ന

A R  $\Box \supset$ 

zΗ

< <

⊢ш

мщ

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat

