navigo

10VS

Open FiberglassTenders





Overal Length	:	10′6″/ 3.19m	Number of Chambers	:	3 + 1	Shaft Length	: 15
Overal Beam	:	5′7″/ 1.72m	Person Capacity	:	5	RDC Design Category	: C
Inside Length	:	7′7″/ 2.31m	Weight	:	169lb / 77kg		
Inside Beam	:	2′8″/ 0.81m	Recommended HP	:	15hp / 11.2kw		
Tube Diameter	:	17"/ 0.43m	Maximum HP	:	25hp / 18.7kw		

A A \forall \vdash \sqcup SH

Δш

0 н

ے

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat with Vent
- Bow Locker Storage to Fit a 6 Gal Portable Fuel Tank.
- Diamond Shape Non Skid Deck

- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
 Orca (CSM) Five Layer Coated Fabric
 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Raised Single Solid Rub Rail
 Stainless Stag
- Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 2 Inside Stern 2 Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams Oarlock Bases

- Telescopic Oars with Aluminum Shaft
 Paddle Holders
 Removable Rowing Seat

- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor Hidden Channel for Fuel Fittings with SS Starburst

: 15" / 38.1cm

- Portable 6 gal Fuel Tank Installed in Bow Locker with Fittings
- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- **Chock Set**
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat

- Removable Stern Seat
- Bimini Top
- Fiberglass Console
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

