

lammina

8UL

Ultra Light Aluminum Tenders



| | Overal Length | : | 8′ 5″/ 2.56m | Number of Chambers | : | 2 | Shaft Length | : 15″/38.1cm |
|--------|---------------|---|--------------|--------------------|---|-------------|---------------------|--------------|
| S | Overal Beam | : | 4′11″/ 1.50m | Person Capacity | : | 4 | RDC Design Category | / :C |
| ш | Inside Length | : | 5'10"/ 1.79m | Weight | : | 68lb / 31kg | | |
| S P | Inside Beam | : | 2′2″/ 0.66m | Recommended HP | : | 4hp / 3.0kw | | |
| | Tube Diameter | : | 16″/ 0.41m | Maximum HP | : | 5hp / 3.8kw | | |

- Shallow "V" Marine Grade Aluminum Hull
 Non-Skid Bubber Floor Percent
- Plastic External Transom Plate
- Aluminum Internal Transom Plate With Security Lip Aluminum Bow Eye
 Aluminum Bow tit Lifting Points
 Aluminum Bow Towing Rings
 Deck Drain with Plug
 Orca (CSM) Five Layer Coated Fabric

ΔS

പ ന

Чĸ

z⊢ ⋖⋖

⊢ш чг

പ ഗ < ш Zœ

o⊃

- ----

- ∢ പപ Ош

- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes
 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
 3 Layer Reinforced Seams
 Removable Rowing Seat

- Oarlock Bases
 Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit

- Tube Chaps
- Boat Cover
- Chock Set

