

# ventus

12VL

Lightweight Fiberglass Tender

OPTIONAL BOW STEP



S P E C S

Overall Length	: 12' / 3.66m	Number of Chambers	: 3 + 1	Shaft Length	: 15" / 38.1cm
Overall Beam	: 5'11" / 1.77m	Person Capacity	: 6	RDC Design Category	: C
Inside Length	: 8'9" / 2.67m	Weight	: 156lb / 71kg		
Inside Beam	: 2'9" / 0.84m	Recommended HP	: 20hp / 14.9kw		
Tube Diameter	: 18" / 0.46m	Maximum HP	: 30hp / 22.4kw		

S T A N D A R D  
F E A T U R E S

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull
- Non - Skid Rubber Floor Pannels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Stainless Steel Bow Eye
- Stainless Steel 3 Davit Lifting Points
- Inner Hull Drain with Plug
- Deck Condensation Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
- Removable Stern Seat
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams

O P T I O N A L  
F E A T U R E S

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

