

## lammina

## 7.5UL

## Ultra Light Aluminum Tenders



	Overal Length	:	7′ 10″/ 2.39m	Number of Chambers	:	2	Shaft Length	:15″/38.1cm
S	Overal Beam	:	4′11″/ 1.50m	Person Capacity	:	3	RDC Design Category	: C
S P E	Inside Length	:	5′5″/ 1.65m	Weight	:	66lb / 30kg		
	Inside Beam	:	2′2″/ 0.66m	Recommended HP	:	3hp / 2.2kw		
	Tube Diameter	:	16″/ 0.41m	Maximum HP	:	4hp / 2.9kw		

- Shallow "V" Marine Grade Aluminum Hull
  Non-Skid Rubber Floer Perto
- Plastic External Transom Plate
- Aluminum Internal Transom Plate With Security Lip
- Aluminum Bow Eye
  Aluminum Bow tit Lifting Points
  Aluminum Bow Towing Rings
  Deck Drain with Plug
  Orca (CSM) Five Layer Coated Fabric

ND

പ ന

Чĸ

 $\Box \supset$ 

z⊢ ∢∢

ーш ωщ

л г < ш Zœ

o⊃

⊢

- ∢ س ہے Оц

- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes Owner's Manual 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes Javer Reinforced Seams Removable Rowing Seat

- Oarlock Bases Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit

Tube Chaps

- Boat Cover
- Chock Set

